



USB 2002 Three CCD Camera System



D&D Video Specialists, LLC

6444 NW Expressway • Suite 209 • Oklahoma City, OK 73132
Tel: 405-720-3180 • Fax: 405-720-3951

Specifications

- Camera head ergonomically designed to fit comfortably in any surgeon's hand



- BF: Body Floating Applied Part
- Remote Head Button
User Selectable For:
Image Capture
White Balance
Gain
- Multiple Peripheral Triggering
- Universal Standard C-Mount



- Direct Connect C-Mount Design
- 17mm Focal Length Lens
- Quick Release Scope Mount
- Ultra Light Compact Design

- Model: 130.2002 CCU 130.1002 Head
- Head: 3-Chip 1/4" CCDs
- 768H x 494V pixels per chip
- C-mount
- 10' or 20' cable
- ETO, Steris and Cidex compatible
- Head Buttons: Programmable
 - Increase/Decrease light
 - Remote 1 & 2
 - White Balance and Gain
 - Zoom in and out
- Horizontal resolution: 850 TVL
- Signal to Noise: 64db
- Sensitivity: 2000 Lux @ F8
- Auto Shutter: 1/60s to 1/50000s
- Zoom: 1x to 1.5x with 45 steps
- Brightness Adjust: 64 steps
- Outputs:
 - 2x composite
 - RGB with separate sync
 - 2x Y/C
 - Firewire
 - USB II
 - DVI Optional
- CCU Functions: White Balance push to set 2800K to 7000K
 - 4 x Preset Procedures including fiber LPF
 - Enhancement up and down 8 steps
 - Gain 0, +5, +10, +15 db
- Remote Controls: 2x dry contacts isolated mini jacks
- Input power: 90 to 264 VAC 50/60 cycles
- UL: 2601-1 UL60601-1
- CCU Dimensions: 12.375" W X 15.622" L X 3.375" H
- Camera head: 3.535" x 1.573"
- Specifications subject to change without notice

Scope, light source and additional accessories available.

For More Information Contact:



D&D Video Specialists, LLC

6444 NW Expressway • Suite 209 • Oklahoma City, OK 73132
Tel: 405-720-3180 • Fax: 405-720-3951