

[> Medical Grade Monitors](#) > EJ-MLB26U-W**EJ-MLB26U-W**26" Class Full HD Widescreen  
Medical Monitor

Contact us for pricing

 **how to buy**• [How To Buy](#) [Larger image](#) [View more images](#) [Print this page](#) [Email this page](#) [View/compare all models](#)

overview

features

<b>Dimensions (H x W x D)</b>	16.14"x 23.58" x 3.93"
<b>Weight</b>	Approx. 8.9 kg
<b>Cabinet Color</b>	White
<b>Size (Diagonal)</b>	25.5 inch
<b>LCD Panel</b>	IPS
<b>View Area</b>	550.1mm x 343.8mm
<b>Aspect Ratio</b>	16:10
<b>Pixel</b>	1920x1200
<b>Number of Colors</b>	16.77 million
<b>Luminance</b>	400 cd/m2 (panel spec.)
<b>Contrast</b>	1000:1 (panel spec.)
<b>Response Speed: Rise: Black-&gt;White; Fall: White- &gt;Black</b>	5ms (Gray to Gray panel spec.)
<b>IPS</b>	Wide view angle with IPS panel
<b>HD Dual Input</b>	HD-SDI 2 input/DVI-D 2 input: Independent display mode
<b>OSD Language</b>	Italian/Spanish/English/German/French/Japanese
<b>HD/SD-SDI</b>	2 input, BNC x 2
<b>DVI-D</b>	2 input, 24 pinx2 with HDCP
<b>HD15</b>	1 input, Dsub 15 pin
<b>Y/Pb/Pr/RGBS</b>	1 input, BNC x 5, Y/G, Pb/B, Pr/R, CSYNC/HD, VD
<b>Video</b>	1 input, BNC x 1
<b>Y/C</b>	1 input, miniDIN 4 pin x 1
<b>Remote</b>	RS-232C (1 connector, Dsub 9 pin) GPI (1 connector, Dsub 9 pin)
<b>Frequency</b>	Horizontal: 31.5~67.5kHz, Vertical: 50.0~60.0Hz
<b>Dot Clock</b>	25~165MHz
<b>Signal Level: HD/SD-SDI</b>	SMPTE274M/296M/259M-C/ITUR BT.656-4
<b>Signal Level: DVI-D</b>	TMDS single link
<b>Signal Level: HD15</b>	R/G/B: 0.7Vpp, HD/VD: TTL
<b>Signal Level: Y/Pb/Pr/RGBS</b>	R/G/B: 0.7Vpp, HD/VD: TTL, Y: 1Vpp, Pb: 0.7Vpp, Pr: 0.7Vpp
<b>Signal Level: Video</b>	1 Vpp
<b>Signal Level: Mounting VESA</b>	100x100 mm, 100x200 mm
<b>Signal Level: Y/C</b>	Y: 1Vpp, C: 0.286Vpp (NTSC Burst), 0.3Vpp (PAL Burst)
<b>Compliance</b>	UL60601-1, CAN/CSA No 601.1, EN60601-1 FDA/MDD Class
<b>Dual display</b>	PIP, POP
<b>Flip display</b>	Mirror, 180° rotation
<b>View Angle (CR&gt;10)</b>	V: 178° / H: 178° (panel spec.)
<b>Output HD/SD-SDI</b>	2 output, BNCx2
<b>Output DVI-D</b>	2 output, When HDCP signal in, no output.
<b>Output YPbPr/RGBS</b>	1 output, BNCx5, Y/G, PB/B, PR/R, CSYNC/HD, VD
<b>Output Video</b>	1 output, BNCx1
<b>Output Y/C</b>	1 output, mini DIN 4pinx1
<b>Output DC OUT</b>	5 V 1 A
<b>Attachment</b>	AC Adapter, AC Cable, DC Cable, Warranty Certificate, Operating Instruction (English, Spanish, French), Installations note, Screw for LCD Arm Installation, Clamper for AC code, Screw for clamper
<b>POWER (AC Adapter)</b>	DC24 V 5.0 A DC5 V 0.03 A
<b>Dimension (W x H x D)</b>	599 mm x 410 mm x 100 mm
<b>AC IN</b>	AC100 V ~ 240 V 50 Hz / 60 Hz 1.6 A ~ 0.6 A
<b>DC OUT</b>	24 V 5.0 A 5 V 0.03 A
<b>AC Adapter Dimension (Wx Hx D)</b>	232 mm x 51 mm x 183 mm
<b>AC Adapter Weight</b>	Approx. 1.7 kg

Features, specifications & pricing subject to change without notice.  
 Copyright © 2009 Panasonic Corporation of North America. All rights reserved.  
 \*\*\* See Online Privacy Policy \*\*\*